



MAIN TECHNICAL DATA	
MAX. WORKING LOAD	55 kN
MAX. HOISTING LOAD	42 kN
MIN. LIFT LOAD	26 kN
LOWERING LOAD	55 kN
CAPACITY OF WINCH	4.5 m
HOISTING SPEED OF BOAT	>3 m/min
SIZE OF WIRE OF WINCH	8X19-18-1778 GALV. NON-TWIST.
MODEL NO.	Y160M-4-H
ELECTRICAL MOTOR	380V/4.5V 50 Hz 1kW
VOLTAGE	440V
FREQUENCY	60 Hz
OUTPUT	1kW

NO.	CODE	NAME	QTY	NATIONAL STANDARD	REMARK
11	23XW G88M7-46	鋼 rivet	12	NY12	
16		鋼 NAME PLATE	1	TC100911	
15		鋼板 OPERATION PLATE	1	TC100911	

NO.	CODE	NAME	QTY	NATIONAL STANDARD	REMARK
1	HWSS-11-0	鋼板 PIVOT UNIT	2	ASSH	
2	HWSS-12-0	鋼板 HYDRAULIC WINCH	1	ASSH	
3	HWSS-13-0	鋼板 PIPE ARRANGEMENT	1	ASSH	
4	HWSS-14	鋼 STOP PLATE	2	ASSH	
5	HWSS-15-0	鋼 DAVIT ARM	1	ASSH	
6	HWSS-16-0	鋼板 GRIPPING UNIT	2	ASSH	
7	HWSS-17-0	鋼 RAMP	1	ASSH	
8	HWSS-18	鋼 HANDLE CROSS BEAM	1	ASSH	
9	HWSS-19-0	鋼 RAMP SUPPORT	2	ASSH	
10	HWSS-20-0	鋼板 RELEASE HOOK	1	ASSH	
11	HWSS-21-0	鋼板 AFT LASHING UNIT	1	ASSH	
12	HWSS-22-0	鋼板 FLOATING UNIT	1	ASSH	
13	HWSS-23-0	鋼 POWER RACKER	1	ASSH	

表仕様
本装置は「1974年國際海上人命安全公約」(SOLAS) (66) 及
國際海上人命安全公約 (MSC48 (66)) に準拠
TECHNICAL REQUIREMENT
THE APPLIANCE CONFORM TO 1974 SOLAS (MSC/L7 (66)) AND
INTERNATIONAL USA CODE (MSC.4/86(6))

SSON 鋼板規格		鋼板規格		鋼板規格	
NO.	CODE	NAME	QTY	NATIONAL STANDARD	REMARK
1	HWSS-11-0	鋼板 PIVOT UNIT	2	ASSH	

GENERAL ARRANGEMENT		鋼板規格		鋼板規格	
NO.	CODE	NAME	QTY	NATIONAL STANDARD	REMARK
1	HWSS-40	鋼板	1	ASSH	